

POWERSTAR PSG-40TL 40kW(50Hz)

1500RPM Golden Series

Generator Specifications

Output	40 kW
Voltage	400V
Phase	Three-phases
Weight	799kg
Frequency	50 Hz
Revolution	1500 rpm
Dimension	1950*880*1040mm



Alternator Specifications

Frequency	50 Hz
Voltage	400v
Power	52.5kVA


Diesel Engine Specifications

Output	60kW
Revolution	1500 rpm
Cylinder	4
Aspiration	Self-priming
Bore	108mm
Stroke	115mm
Weight	310 kg

Controller Specifications

Working Voltage	8.0V-35.0V DC Continuous power supply
Power Consumption	< 3W(Standby ≤ 2W)
Overall Dimension	135mm*110mm*44mm
Installation	116mm*90mm










POWERSTAR PSG-40TL

40kW(50Hz)








Installation Dimention

Exhaust Pipe mm	90	
Water Inlet Pipe mm	45	
Oil Inlet Pipe mm	10	
Oil Return Pipe mm	10	
Battery Capacity AH	100	



Standard Configuration



- Remote Panel
- Oil Water Separator
- 15m Remote Cable
- Water Intake
- Sea Water Filter
- Muffler
- Generator Self-protection Shutdown: High water temperature, low oil pressure, high speed